

AVL-55 Data Sheet



Vehicle Tracking Device

The AVL-55 is a mini GPS tracker designed for a wide variety of vehicle tracking applications. It has multiple I/O interfaces that can be used for monitoring or controlling external devices. Its built-in GPS receiver has superior sensitivity and fast time to first fix. Its quad band GPRS/GSM subsystem supports 850/900/1800/1900 MHz allowing the AVL-55's location to be monitored in real time or periodically tracked by a backend server and mobile devices. Its built-in 3-axis accelerometer allows motion detection and extends battery life through sophisticated power management algorithms. System integration is straightforward as complete documentation is provided for the full featured @Track protocol. The @Track protocol supports a wide variety of reports including emergency, geo-fence boundary crossings, driving behavior, low battery and scheduled GPS position.

Highlights

- Driving Behavior Monitoring and Incident Notification
- Designed for Insurance and Car Leasing / Rental Applications
- Small Size Allowing Easier Installation

Advantages

- Extremely compact enclosure 63mm*50mm*21.8mm
- Internal 3-axis accelerometer supporting driving behavior monitoring, power saving and motion detection
- Internal u-blox chipset
- Low power consumption, long standby time with internal battery
- Quad band GSM/GPRS 850/900/1800/1900 MHz
- Embedded full featured @Track protocol
- Multiple I/O interfaces for monitoring and control
- Internal GSM antenna
- Internal GPS antenna
- CE/FCC/E-Mark/Anatel certified

AVL-55

Vehicle Tracking Device



GSM Specification

Frequency	Quad band: 850/900/1800/1900 MHz Compliant to GSM phase 2/2+ -Class 4 (2W @ 850/900 MHz) -Class 1 (1W @ 1800/1900 MHz)
GPRS	GPRS multi-slot class 10 GPRS mobile station class B
RMS Phase Error	5 deg
Max Out RF Power	GSM850/GSM900: 33.0±2 dBm DCS/PCS: 30.0±2 dBm
Dynamic Input Range	-15 ~ -108 dBm
Receiver Sensitivity	Class II RBER 2% (-107 dBm)
Stability Of Frequency	< 2.5 ppm
Max Frequency Error	\pm 0.1 ppm



General Specification

Dimensions	63mm*50mm*21.8mm
Weight	50g
Backup Battery	Li-Polymer 250 mAh
Standby Time	Without reporting: 59 hours 5 minutes reporting: 35 hours 10 minutes reporting: 45 hours
Operating Voltage	8V to 32V DC
Operating Temperature	-30°C ~ +80°C -40°C ~ +80°C for storage

GPS Specification

GPS Chipset	56-channel u-blox All-In-One GPS receiver
Sensitivity	Autonomous: -147 dBm Hot start: -156 dBm Reacquisition: -160 dBm Tracking: -162 dBm
Position Accuracy (CEP)	Autonomous: < 2.5m SBAS: < 2.0m
TTFF (Open Sky)	Cold start: 27s average Warm start: 27s average Hot start: 1s average

Air Interface Protocol

Transmit Protocol	TCP, UDP, SMS
Power Supply Monitoring	Alarm status reporting of the external power and backup battery of the device
Scheduled Report	Report position at a preset time interval, distance, mileage or combination of these values
Geo-fence	Geo-fence alarm and parking alarm, support up to 20 internal geo-fence regions
Tow Alarm	Alarm report for movement when ignition is off
Speed Alarm	Flexible speed monitoring for unusual speed alarm
Driving Behavior Monitoring	Aggressive driving behavior detection, e.g. harsh braking and acceleration
Crash Detection	Accident data collection for reconstruction and analysis
Special Alarm	Special alarm based on the digital inputs
Remote Control	OTA control of device outputs

Interfaces

Digital Inputs	Two digital inputs One positive trigger for ignition detection One negative trigger input for normal use
Digital Outputs	One digital output, open drain, 150 mA max current drain
Latched Digital Outputs	One digital output with internal latch circuit, open drain, 150 mA max current drain
GSM Antenna	Internal only
GPS Antenna	Internal only
Indicator LED	GSM, GPS and power
Mini USB Port	Mini USB port for upgrading and debugging



www.TrackingTheWorld.com

1633 Bayshore Hwy, Suite 390, Burlingame, CA. 94010 **Sales:** (650) 692-8100

Technical Support: (650) 692-2876