



WT-OBD

Data Sheet



OBDD Vehicle Tracking Device

The WT-OBD is a vehicle tracking device that plugs into a vehicle's OBDII port. Its compact design allows easy installation. Its internal OBD reader can obtain information from the vehicle's on-board computer and relay it over GPRS networks. Its built-in GPS receiver has superior sensitivity and fast time to first fix. Its quad band GPRS/GSM subsystem supports 850/900/1800/1900 MHz allowing the WT-OBD's location to be monitored in real time or periodically tracked by a backend server and mobile devices. Its built-in 3-axis accelerometer allows motion detection. System integration is straightforward as complete documentation is provided for the full featured @Track protocol. The @Track protocol supports a wide variety of reports including emergency, geo-fence boundary crossings, low battery and scheduled GPS position.

Highlights

- Compact Design, Plug and Play
- Real Time Vehicle Status Monitoring From OBD Port
- Wide Operating Voltage Range 8V to 32V DC
- Perfect for Insurance and Car Leasing / Rental Applications

Advantages

- OBDII connectivity, easy to install
- Quad band GSM/GPRS frequencies 850/900/1800/1900 MHz
- Wide operating voltage range 8V to 32V DC
- Internal u-blox chipset
- Embedded full featured @Track protocol
- Internal 3-axis accelerometer for power saving and motion detection
- Internal GSM antenna
- Two internal GPS antennas, automatically use the one with better signal
- FCC/CE/E-Mark certified

WT-OBD

Vehicle Tracking Device



GSM Specification

Frequency	Quad band: 850/900/1800/1900 MHz Compliant to GSM phase 2/2+ -Class 4 (2W @ 850/900 MHz) -Class 1 (1W @ 1800/1900 MHz)
GPRS	GPRS multi-slot class 12 GPRS mobile station class B
RMS Phase Error	5 deg
Max Out RF Power	GSM850/GSM900: 33.0 ± 2 dBm DCS/PCS: 30.0 ± 2 dBm
Dynamic Input Range	-15 ~ -108 dBm
Receiver Sensitivity	Class II RBER 2% (-107 dBm)
Stability Of Frequency	< 2.5 ppm
Max Frequency Error	± 0.1 ppm

General Specification

Dimensions	48mm*25mm*48mm
Weight	About 48g
Backup Battery	Li-Polymer 130 mAh
Operating Voltage	8V to 32V DC
Operating Temperature	-30°C ~ +80°C (without battery) -40°C ~ +85°C for storage (without battery)

GPS Specification

GPS Chipset	56-channel u-blox All-In-One GPS receiver
Sensitivity	Autonomous: -147 dBm Hot start: -156 dBm Reacquisition: -160 dBm Tracking: -162 dBm
Position Accuracy (CEP)	Autonomous: < 2.5m SBAS: < 2.0m
TTF (Open Sky)	Cold start: 27s average Warm start: 27s average Hot start: 1s average

Air Interface Protocol

Transmit Protocol	TCP, UDP, SMS
Scheduled Timing Report	Report position and status at preset intervals
OBDII Disconnection Alarm	Alarm report of OBDII connection and disconnection status
Geo-fence	Geo-fence alarm and parking alarm, support up to 5 internal geo-fence regions
Low Power Alarm	Alarm when backup battery is low
Power On Report	Report when the device is powered on
Tow Alarm	Alarm trigger based on built-in 3-axis accelerometer

Interfaces

OBDII Port	Allow information to be read from OBDII port, and provide device power. Support legislated OBDII protocols: J1850 PWM, J1850 VPW, ISO 9141-2, ISO 14230, ISO 15765-4, J1939
GSM Antenna	Internal only
GPS Antenna	Internal only
Indicator LED	CEL, GPS and OBD
Mini USB Port	Mini USB port for upgrading and debugging



TrackingTheWorld
GPS Tracking Solutions

www.TrackingTheWorld.com

1633 Bayshore Hwy, Suite 390, Burlingame, CA. 94010

Sales: (650) 692-8100

Technical Support: (650) 692-2876